



compensation and waveform coding field by field.

In recent years, for reproducing an image signal for each of objects in a frame image while increasing efficiency in compressing an image signal, a coding method has been conceived, wherein image signals of the objects are compressively coded and transmitted separately for each object. A coded image signal which has been coded by this coding method is decoded at the reproducing end in a manner adapted to the coding method. Specifically, in this decoding, coded image signals of respective objects are decoded, and the resulting decoded image signals of respective objects are synthesized, to produce a reproduced image signal. Then, based on the reproduced image signal, a frame image comprising respective objects is displayed.

Technology Center 2609

MAR 22 2002

RECEIVED

By using the coding method for performing coding to the image signal for each object as described above, it becomes possible to combine objects freely to generate a composite image, whereby moving images can be reedited with ease. In addition, a moving image comprising only objects with high importance can be displayed without reproducing objects with relatively low importance, depending on ^{va} degree of congestion of a communication path, performance of a reproducing apparatus, or preference of a viewer.

For coding an image signal of an object, (an image having an arbitrary shape), ^{va} waveform transform which performs

signal processing adapting to a shape of the object, for example, shape adaptive DCT, or waveform transform to a padded image signal, is employed. In the method, specifically, padding is performed to an image signal forming an image space (rectangular region) by replacing values of pixels in its insignificant region with padding pixel values obtained by a prescribed method, and then ^{V^a}conventional 8 x 8 cosine transform is performed to the padded image signal. The insignificant region is a region outside an object in the rectangular region, and comprises pixels which have no values for displaying the object. In other words, an image signal of the insignificant region comprises so-called insignificant sample values. Also, the 8 x 8 cosine transform is ^{V^a}waveform transform which performs cosine transform to the image signal of the rectangular region for each image space comprising 8 x 8 pixels.

As a method for eliminating redundant signal ^{V^s} between adjacent frames, there is a method for obtaining ^{V^a}difference between an image signal of a target macroblock to be coded and its prediction signal for each image space (macroblock) comprising 16 x 16 pixels, as a prediction error signal (difference signal). Here, it is assumed that the prediction signal is an image signal of ^aan prediction region obtained by motion compensation. The motion compensation process detects a region comprising 16 x 16 pixels

corresponding to an image signal in a coded or decoded frame where \sqrt{A} difference between the image signal of the target macroblock and the image signal is the smallest, as a prediction region.

In some cases, however, the prediction region also includes pixels (hereinafter referred to as insignificant pixels) which have insignificant sample values. In such cases, when the difference between the prediction signal of the prediction region including insignificant values and an image signal of the target region is computed, difference values tend to be very large, since the sample values of the insignificant pixels are not always optimal prediction values for smaller difference.

As a solution to this, padding is performed to the image signal of the prediction region by replacing insignificant sample values by prescribed padding values, and then \sqrt{A} difference between the padded prediction signal and the image signal of the target macroblock is computed as a difference signal (prediction error signal), which is subjected to transformation for coding. This Padding of the prediction signal can suppress the difference signal.

In the prior art pixel value padding, as a padding value for an insignificant sample value, sample values of significant values (pixels having significant sample values) adjacent to the corresponding insignificant pixel in the

vertical and horizontal directions, respectively, are averaged, and the resulting average is used. By the use of the average of the sample values of the significant pixels, high-frequency components into an image signal (prediction signal) in a padded image space can be suppressed, thereby increasing coding efficiency.

However, if padding which uses the average of the significant pixels adjacent to the insignificant pixels in the vertical and horizontal directions as the padding value is applied to the image signal of the interlaced image, high-frequency components of the image signal increase, which will be described below in detail.

In the interlaced image, especially in a case where motion of an object is large, there is low correlation of pixel values between adjacent scanning lines. Figure 18 schematically shows an example of arrangement of pixel values which shows ^{van}~~the~~ low correlation of pixel values between adjacent scanning lines in the interlaced image, as arrangement of pixel values in an image space 301.

The image space 301 is an image space comprising 8 x 8 pixels. In the figure, each pixel is represented as a square. Pixels (for example pixels 303 and 304) of hatched squares are pixels (significant pixels) having significant sample values, and pixels (for example pixel 302) of squares which are not hatched are pixels (insignificant pixels)

having insignificant pixels. The number of each square indicates a sample value of the corresponding pixel.

Since scanning timings differ from each other between odd-numbered and even-numbered fields in the interlaced image, in a case where motion of an object in an image is large, it looks like the object has a shape of two outlines in a frame composed of these two fields, as it can be observed in the image space 301 in figure 18. In this case, for example, the significant pixel 304 is adjacent to its upper and lower insignificant pixels.

Next, a prior art padding method and its ^{padding} adding result will be described with reference to figures 18 and 19.

In the prior art padding method, three steps are performed.

In a first step S1, sample values of insignificant pixels are replaced with sample values of significant pixels adjacent thereto in the image space 301, for insignificant pixels aligned in the horizontal direction, in the order from inward to outward of the image space 301. Then, sample values of insignificant pixels in the image space to which this horizontal replacement process has been performed are replaced with sample values of significant pixels adjacent thereto, for insignificant pixels aligned in the vertical direction, in the order from inward to outward of the image space. Process in the first step S1 thus performed to the

in figure 18.

More specifically, in the vertical replacement process in the second step S2, sample values of insignificant pixels on pixel columns 362-365 are replaced with padding values in the image space 351. In addition, in the horizontal replacement process in the second step S2, sample values of insignificant pixels on pixel columns 360 and 361 are replaced with sample values of significant pixels and padded pixels on the pixel column 362, and likewise, sample values of insignificant pixels on pixel columns 367 and 368 are replaced with sample values of significant pixels and padded pixels on the pixel column 365.

In a third step S3, as shown in figure 19, sample values of pixels in the image space 350 obtained through the first step S1 and the corresponding pixels in the image space 351 obtained through the second step S2 are averaged, which results in an image space 380 comprising pixels having sample values in figure 19.

Resampling which divides pixels forming the image space 380 into pixels corresponding to odd-numbered and even-numbered fields ^{based} on assumption that the image space 380 is a frame, results in an image space 381 comprising plural pixels corresponding to the odd-numbered field and an image space 382 comprising plural pixels corresponding to the even-numbered field as shown in figure 20. In the image

spaces 381 and 382 corresponding to these respective fields, sample values of pixels are non-uniform, which introduces high-frequency components into image signals in image spaces 381 and 382.

In addition, this problem associated with the padding occurs in the non-interlacing scanned image (progressive image) as well as in the interlacing scanned image (interlaced image). Specifically, in many cases, the progressive image has a stripe pattern, and for the case of the progressive image having the stripe pattern, the above resampling is performed in such a manner that plural pixels forming a frame (image space) are collected into a stripe portion and the other portion in the image space, to form image spaces corresponding to the stripe pattern portion and the other portion, and then the resulting resampled image spaces are coded.

In this case, if padding is performed to the image signal of the progressive image having the stripe pattern by the prior art padding method, high-frequency components are introduced into an image signal corresponding to the resampled image space, leading to degraded coding efficiency.

Further, ^a~~the~~ similar problem occurs in padding methods other than the above, which computes padding values using significant sample values adjacent to insignificant pixels

in the horizontal or vertical direction.

The present invention is directed to solving the above-mentioned problem and has an object to provide a digital image padding method in which padding is performed to an interlacing scanned image or an image of a stripe pattern having an arbitrary shape while suppressing degradation of efficiency in coding the prediction error signal, an image processing apparatus which performs image coding or image decoding by the padding method, and a data recording medium which contains a program for implementing these image processing by the padding method or the image processing apparatus in a computer.

Summary
Disclosure of the Invention
a first aspect

According to ~~claim 1~~ of the present invention, a digital image padding method *is provided* ~~of the present invention~~ for performing padding of pixel values to a digital image signal forming an original image space comprising an image having an arbitrary shape and comprising significant pixels and insignificant pixels, comprises a pixel rearrangement step in which plural pixels in the original image space are grouped according to a prescribed rule, to form plural small image spaces each comprising pixels of the same group; and a pixel padding step in which values of insignificant pixels in each small image space are replaced with padding pixel values

generated by a prescribed method.

In the digital image padding method thus constructed, plural pixels forming the original image space are extracted according to a prescribed rule, to form plural small images. In other words, it is possible to divide the original image space where there is low correlation of pixel values between adjacent pixels or scanning lines into plural small images where there is high correlation of pixel values between the adjacent pixels or scanning lines. Accordingly, padding is performed to the interlacing scanned image or the image of a stripe pattern having an arbitrary shape for each small image space with high correlation of the pixel values rather than the original image space with low correlation of pixel values between adjacent pixels or scanning lines. In this case, in the padded small image, there is high correlation of the pixel values, and it is possible to avoid introduction of high-frequency components into the image signal corresponding to the original image space in process for padding the interlacing scanned image or the image of a stripe pattern having an arbitrary shape.

As a result, differential coding or differential decoding is performed to the interlacing scanned image while suppressing degradation of coding efficiency resulting from the padding.

a second aspect
According to ~~claim 2~~ of the present invention, in the

the first aspect of the invention
 digital image padding method of ~~claim 1~~, in the pixel rearrangement step, sampling is performed by extracting pixels every $(N + 1)$ -th (N : positive integer) pixel in a prescribed direction of the image space $(N + 1)$ times by using the first to the $(N + 1)$ -th pixels as starting sample pixels, to form $(N + 1)$ pieces of small image spaces each comprising a prescribed number of pixels obtained by one sampling.

In the digital image padding method thus constructed, pixels in the original image space are extracted at intervals of a prescribed number of pixels in a prescribed direction of the original image space, to form the small image spaces. Therefore, it is possible to divide the original image space comprising an image having an arbitrary shape of a vertical stripe pattern or a horizontal stripe pattern into small image spaces where there is high correlation of pixel values between adjacent pixel rows or between adjacent pixel columns, irrespective of a width or arrangement spacing of stripes.

a third aspect
 According to ~~claim 3~~ of the present invention, in the digital image padding method of ~~claim 2~~, *the second aspect of the invention* operation values obtained by performing operation on values of significant pixels in an N -th ($n=1, 2, \dots, N+1$) small image space are used as the padding pixel values for replacing the values of insignificant pixels in the n -th small image space.

In the digital image padding method thus constructed, values of insignificant pixels in a small image space are

replaced with padding pixel values obtained from values of significant pixels in the same small image. Therefore, it is possible to suppress generation of pixel values which are significantly different from values of significant pixels in the small image space in padding process.

According to ~~claim 4~~ ^{a fourth aspect} of the present invention, the digital image padding method of ~~claim 2~~ ^{the second aspect of the invention} further comprises an image space restoring step in which plural pixels forming padded small image spaces are rearranged following a rule adapted to the prescribed rule of the grouping so that these pixels forms a restored image space which has the same pixel rearrangement as the original image space.

In the digital image padding method thus constructed, after the original image space is divided into plural small images where there is high correlation of pixel values, and padding of pixel values is performed to these small image spaces, pixels in the padded small image space are rearranged so that they have the same arrangement as the original image space. Therefore, the image signal corresponding to the padded original image space can be processed in the same manner that the image signal corresponding to the unpadded original image space is processed.

According to ~~claim 5~~ ^{a fifth aspect} of the present invention, in the digital image padding method of ~~claim 4~~ ^{the fourth aspect of the invention}, operation values obtained by performing operation on values of significant

pixels in an n-th ($n=1, 2, \dots, N+1$) small image space are used as the padding pixel values for replacing the values of insignificant pixels in the n-th small image space.

In the digital image padding method thus constructed, values of insignificant pixels in a small image space are replaced with padding pixel values obtained from values of significant pixels in the same small image space. Therefore, it is possible to suppress generation of pixel values which are significantly different from values of significant pixels in the small image space in padding process.

According to ^{a sixth aspect} ~~claim 6~~ of the present invention, in the digital image padding method of ^{the first aspect of the} ~~claim 1~~ invention, in the pixel rearrangement step, sampling is continuously performed twice using the first and second pixel rows as starting sample pixel rows, by extracting pixels on every other pixel row in the vertical direction of the original image space, to form first and second small image spaces each comprising a prescribed number of pixels obtained by the first and second samplings, respectively.

In the digital image padding method thus constructed, every other pixels are extracted in the vertical direction of the original image space, to form a small image space composed of odd-numbered scanning lines in the original image space and a small image space composed of even-numbered scanning lines and a small image space composed of even-

numbered scanning lines. Therefore, padding of the interlacing scanned image is performed for each small image space corresponding to each field where there is high correlation of pixel values between adjacent scanning lines rather than the original image space where there is low correlation of pixel values between them. As a result, it is possible to avoid introduction of high-frequency components into an image signal of the interlacing scanned image in padding process.

a general aspect
According to ~~claim 7~~ of the present invention, a digital image padding method for performing padding of pixel values to a digital image signal forming an original image space comprising an image having an arbitrary shape and comprising significant pixels and insignificant pixels, comprises the steps of dividing the original image space into a first small image space comprising pixels on odd-numbered pixel rows in the original image space and a second small image space comprising pixels on even-numbered pixel rows in the original image space; and generating first padding pixel values from values of significant pixels in the first small image space and replacing values of insignificant pixels in the first small image space with the first padding pixel values, and generating second padding pixel values from values of significant pixels in the second small image space and replacing values of insignificant pixels in the second small

image space with the second padding pixel values.

In the digital image padding method thus constructed, padding of the interlacing scanned image is performed for each of first and second small image spaces corresponding to fields where there is high correlation of pixel values between adjacent scanning lines rather than the original image space where there is low correlation of pixel values between them. As a result of this, it is possible to avoid introduction of components into an image signal of the interlacing scanned image in padding process.

Besides, values of insignificant pixels in each small image space are replaced with padding pixel values obtained from values of significant pixels in the same small image space, and it is therefore possible to suppress generation of pixels values which are significantly different from values of significant pixels in the small image space in padding process.

According to ~~claim 6~~ *an eighth aspect* of the present invention, a digital image padding method for performing padding to a digital image signal forming an original image space comprising an image having an arbitrary shape and comprising significant pixels and insignificant pixels, by replacing values of insignificant pixels with padding pixel values determined from values of significant pixels in the original image space, wherein, significant pixels which have values used for

determining the padding pixel values are pixels other than pixels adjacent to insignificant pixels to be padded.

In the digital image padding method thus constructed, the padding pixel values for replacing values of insignificant pixels are determined from values of significant pixels other than pixels adjacent to the insignificant pixels in the original image space, and therefore the values of the insignificant pixels are not replaced with the values of the pixels adjacent thereto. As a result, it is possible to perform padding of pixel values to the original image space where there is low correlation of pixel values between adjacent pixels or scanning lines while suppressing introduction of high-frequency components into the image signal corresponding to the original image space.

a ninth aspect
According to ~~claim 9~~ of the present invention, in the digital image padding method of ~~claim 8~~, *the eighth aspect of the invention* significant pixels which have values used for determining the padding pixel values are one pixel apart from the insignificant pixels to be padded.

In the digital image padding method thus constructed, values of insignificant pixels on an odd-numbered scanning line are replaced with padding pixel values obtained from values of significant pixels on another odd-numbered scanning line in the original image space, and values of

insignificant pixels on an even-numbered scanning line are replaced with padding pixel values obtained from values of significant pixels on another even-numbered scanning line in the original image space. Therefore, it is possible to avoid introduction of high-frequency components into the image signal corresponding to the interlacing scanned image in padding process.

According to ^{a tenth aspect} ~~claim 10~~ of the present invention, an image processing apparatus for performing image coding which comprises ^a correlation identifying ^{device} ~~means~~ for identifying correlation between pixel values of a digital image signal and outputting a sample identifier according to the identification result, a coding section for performing differential coding to the digital image signal by the use of a prediction image signal of the digital image signal according to the sample identifier and outputting a coded image signal, and a predicting section for producing the prediction image signal based on a decoded image signal in which the coded image signal has been locally decoded, the coding section comprises a subtracter for computing difference between the digital image signal and the prediction image signal as a difference signal; ^a data compressing ^{device} ~~means~~ for compressing the difference image signal to produce a compressed image signal; and a variable length encoder for performing variable length coding to the

compressed difference signal, and the predicting section comprises ^{va} data expanding ^{device} means for expanding the compressed difference signal to produce an expanded difference signal; an adder for adding the expanded difference signal to the prediction image signal to produce a decoded image signal; ^{va} padding ^{device} means for performing padding according to the sample identifier by rearranging pixels in an image space formed by the decoded image signal and replacing values of insignificant pixels in the image space where the pixels have been rearranged with padding pixel values generated by a prescribed method; and ^{va} prediction image signal producing ^{device} means for producing the prediction image signal from the padded decoded image signal according to the sample identifier.

In the digital image processing apparatus thus constructed, the predicting section for producing the prediction image signal of the digital image signal, comprises the padding ^{device} means for performing padding of pixel values to the decoded image signal in which the coded difference signal has been locally decoded in its differential coding process, and is used for producing the prediction image signal from the padded decoded image signal, the padding ^{device} means first rearranging pixel values of the decoded image signal and then replacing the values of the insignificant pixels of the decoded image signal with the

prescribed padding pixel values. Therefore, when performing differential coding to the digital image signal of the interlacing scanned image or the image of a stripe pattern having an arbitrary shape, it is possible in padding process to avoid introduction of high-frequency components into the prediction image signal for use by differential coding, differential coding can be performed to the interlacing scanned image while suppressing degradation of coding efficiency resulting from the padding.

According to ~~claim 11~~ ^{an eleventh aspect} of the present invention, in the image processing apparatus of ~~claim 10~~ ^{the tenth aspect of the invention}, the coding section ^{VA} further comprises ^{device} padding means for performing padding to the difference image signal according to the sample identifier by rearranging pixels in the image space formed by the difference image signal and replacing values of insignificant pixels in the image space where the pixels have been rearranged with padding pixel values generated by a prescribed method, and the data compressing ^{device} means performs information compression to the padded difference image signal to produce a compressed difference image signal.

In the image processing apparatus thus constructed, pixel values of the difference image signal input to the data compressing ^{device} means are rearranged, and then padding is performed by replacing values of the insignificant pixels of the difference signal with the prescribed padding pixel

values. Therefore, it is possible to avoid introduction of high-frequency components into the image signal input to the data compressing means. As a result, when performing differential coding to the digital image signal of the interlacing scanned image or the image of a stripe pattern having an arbitrary shape, waveform transform such as DCT is performed with high efficiency.

According to ~~claim 12~~ ^{a further aspect} of the present invention, an image processing apparatus for performing image decoding which comprises a reproducing section for reproducing a coded image signal in which a digital image signal has been coded by the use of a prediction image signal of the digital image signal and outputting a reproduced image signal, and a predicting section for producing the prediction image signal from the reproduced image signal, and the reproducing section comprise a data analyzing unit for analyzing the coded image signal to extract a compressed difference signal of the digital image signal and a sample identifier indicating correlation between pixel values of the digital image signal from the coded image signal; ^{via} data expanding ^{device} means for expanding the compressed difference signal to produce an expanded difference signal; and an adder for adding the expanded difference signal to the prediction signal to produce the reproduced image signal, and in the predicting section, using at least one of the reproduced image signal

and the prediction image signal obtained from the reproduced image signal as a signal to be padded, padding is performed to the signal to be padded according to the sample identifier, by rearranging pixels in an image space formed by the signal to be padded and replacing values of insignificant pixels in the image space where the pixels have been rearranged with padding pixel values generated by a prescribed method.

8 In the image processing apparatus thus constructed, the predicting section for producing the prediction image signal of the digital image signal comprises ^{an} padding ^{device} means for performing padding of pixel values to the reproduced image signal or the prediction image signal of the digital image signal as the signal to be padded, and the padding process rearranges pixel values of the signal to be padded and then replaces values of insignificant pixels of the signal to be padded with prescribed padding pixel values. Therefore, when decoding a coded difference signal of the interlacing scanned image or the image of a stripe pattern having an arbitrary shape, it is possible to avoid introduction of high-frequency components into the prediction image signal for use by the differential decoding. As a result, differential decoding adapted to differential coding which suppresses degradation of coding efficiency resulting from padding of pixel values, is realized.

a thirteenth aspect
 According to ~~claim 13~~ of the present invention, in the

image processing apparatus of ~~claim 12~~, ^{the twelfth aspect of the invention} the predicting section further comprises ^{va} ~~padding means~~ ^{device} for performing padding to the reproduced image signal frame by frame or field by field according to the sample identifier, and a frame memory for storing a padded reproduced signal in which the reproduced image signal has been padded, and outputs the padded reproduced image signal stored in the frame memory to the reproducing section as the prediction image signal.

In the image processing apparatus thus constructed, padding is performed to the reproduced image signal according to the sample identifier frame by frame or by field by field. Therefore, especially when performing differential decoding to the digital image signal of the interlacing scanned image, it is possible to avoid introduction of high-frequency component into the prediction image signal obtained from the reproduced image signal in padding process.

According to ^{a fourteenth aspect} ~~claim 14~~ of the present invention, in the image processing apparatus of ~~claim 12~~, ^{the twelfth aspect of the invention} the predicting section further comprises a frame memory for storing the reproduced image signal, and ^{va} ~~padding means~~ ^{device} for performing padding to the prediction image signal extracted from the reproduced image signals stored in the frame memory frame by frame or field by field according to the sample identifier, and outputs the padded prediction image signal to the reproducing section.

In the image processing apparatus thus constructed, padding is performed to the prediction image signal according to the sample identifier frame by frame or by field by field. Therefore, especially when performing differential decoding to the digital image signal of the interlacing scanned image, it is possible to avoid introduction of high-frequency components into the prediction image signal in the process for padding the prediction image signal. Besides, since padding is performed only to the prediction signal fetched from the frame memory, amount of signals to be padded in the predicting section can be reduced.

According to ~~claim 15~~ *a fifteenth aspect* of the present invention, an image processing apparatus for performing image decoding, which comprises a reproducing section for reproducing a coded image signal in which a digital image signal has been coded by the use of a prediction image signal of the digital image signal and outputting a reproduced image signal, and a predicting section for producing the prediction image signal from the reproduced image signal, the reproducing section comprises a data analyzing unit for analyzing the coded image signal to extract a compressed difference signal of the digital image signal and a sample identifier indicating correlation between pixel values of the digital image signal from the coded image signal; ^{va} data expanding ^{device} means for expanding the compressed difference signal to produce an expanded

difference signal; and an adder for adding the expanded difference signal to the prediction image signal to produce the reproduced image signal, and the predicting section comprises ^{va}padding ^{device} means for performing padding to the reproduced image signal according to the sample identifier, by replacing values of insignificant pixels in an image space formed by the reproduced image signal with padding pixels values generated from values of significant pixels other than pixels adjacent to the insignificant pixels; and ^{va}rearrangement ^{device} means for rearranging pixels in an image space formed by the padded reproduced image signal, according to the sample identifier.

In the digital image processing apparatus thus constructed, when performing padding to the reproduced image signal obtained from the coded difference image signal containing digital image information, the padding pixel values for replacing values of insignificant pixels are determined from values of significant pixels other than pixels adjacent to the insignificant pixels in the image space formed by the reproduced image signal. Therefore, values of insignificant pixels will not be replaced with values of pixels adjacent thereto. As a result, when performing differential decoding to the digital image signal, it is possible to perform padding of pixel values in the original image space where there is low correlation of pixel

values between adjacent pixels or scanning lines while suppressing introduction of high-frequency components into the image signal in the original image space.

a sixteenth aspect
 4 According to ~~claim 16~~ of the present invention, a data recording medium for storing a program which makes a computer perform padding of pixel values to a digital image signal forming an original image space comprising an image having an arbitrary shape and comprising significant pixels and insignificant pixels, and the program makes the computer perform padding of the pixel values according to the digital image padding method of ~~claim 1~~. *the first aspect of the invention*

12 By loading the program stored in the data recording medium thus constructed into the computer, padding is implemented by the computer without degrading coding efficiency when performing differential coding or differential decoding to the interlacing scanned image or the like.

a seventeenth aspect
 18 According to ~~claim 17~~ of the present invention, a data recording medium for storing a program which makes a computer perform padding of pixel values to a digital image signal forming an original image space comprising an image having an arbitrary shape and comprising significant pixels and insignificant pixels, and the program makes the computer perform padding of pixel values according to the digital image padding method of ~~claim 7~~. *the seventh aspect of the invention*

By loading the program stored in the data recording medium thus constructed into the computer, padding is implemented by the computer without degrading coding efficiency when performing differential coding or differential decoding to the interlacing scanned image.

6 According to ~~claim 18~~ *an eighteenth aspect* of the present invention, a data recording medium for storing a program which makes a computer perform padding of pixel values to a digital image signal forming an original image space comprising an image having an arbitrary shape and comprising significant pixels and insignificant pixels, and the program makes the computer perform padding of pixel values according to the digital image padding method of ~~claim 8~~ *the eighth aspect of the invention*.

14 By loading the program stored in the data recording medium thus constructed into the computer, padding is implemented by the computer without degrading coding efficiency when performing differential coding or differential decoding to the interlacing scanned image.

19 According to ~~claim 19~~ *the nineteenth aspect* of the present invention, a data recording medium for storing a program which makes a computer perform image signal coding, and the program makes the computer perform differential coding to a digital image signal by the image processing apparatus of ~~claim 10~~ *the tenth aspect of the invention*.

By loading the program stored in the data recording medium so constructed into the computer, differential coding

of the interlacing scanned image or the like is implemented by software with no degradation of coding efficiency resulting from padding.

a twentieth aspect
According to ~~claim 20~~ of the present invention, a data recording medium for storing a program which makes a computer perform image signal decoding, and the program makes the computer perform differential decoding to the digital image signal by the image processing apparatus of ~~claim 12~~. *the twelfth aspect of the invention*

By loading the program stored in the data recording medium thus constructed, differential decoding of the interlacing scanned image, which is adapted to differential coding with no degradation in coding efficiency resulting from padding, is implemented by software.

a twentieth aspect
According to ~~claim 21~~ of the present invention, a data recording medium for storing a program which makes a computer perform image signal decoding, and the program makes the computer perform differential decoding to the digital image signal by the image processing apparatus of ~~claim 15~~. *the fifteenth aspect of the invention*

By loading the program stored in the data recording medium thus constructed into the computer, differential decoding of the interlacing scanned image or the like, which is adapted to differential coding with no degradation of coding efficiency resulting from coding, is implemented by software.

Figure 14 is a block diagram showing an image decoding apparatus according to a fourth embodiment of the present invention.

Figure 15 is a block diagram for explaining ^{an} ~~a~~ image decoding apparatus according to a modification 1 of the fourth embodiment.

Figure 16 is a block diagram showing an image decoding apparatus according to a modification 2 of the fourth embodiment.

Figures 17(a), 17(b), and 17(c) are diagrams for explaining a data recording medium which contains a program for implementing image processing by the digital image padding method or in the image processing apparatus, in a computer system.

Figure 18 is a diagram showing replacement of pixel values in a prior art digital image padding method.

Figure 19 is a diagram showing averaging of pixel values in the prior art digital image padding method.

Figure 20 is a diagram showing resampling of pixel values in the prior art digital image padding method.

Description of the Preferred Embodiments ~~Best Mode for Carrying Out the Invention~~

Now, preferred embodiments of the present invention will be described with reference to figures 1-17.

Embodiment 1.

Figures 1-3 are diagrams for explaining a digital image padding method according to a first embodiment of the present invention. Figure 1 shows flow of processing of an image signal in the padding method.

The digital image padding method of the first embodiment, as shown in figure 1, includes resampling an original image space formed by a sampled input image signal to form plural small image spaces (step S12), and performing padding to each of the small image spaces by replacing sample values of insignificant pixels with padding pixel values obtained by a prescribed method.

Figure 2 schematically shows resampling according to the digital image padding method. An original image space 301 corresponding to the input image signal, comprises 8×8 pixels, which are significant pixels having significant sample values and insignificant pixels having insignificant sample values. In figure 2, each pixel is represented by a square. The significant pixels are pixels (for example, pixels 303 and 304) of squares which are hatched, and the insignificant pixels are pixels (for example pixel 302) which are not hatched. The numbers of respective squares indicate the corresponding sample values.

Small image spaces 401-404 resulting from the resampling each comprises 4×4 pixels. In this embodiment, the small image space 401 comprises pixels, which are

Note that the digital image signal may correspond to the interlacing scanned image (interlaced image) or the non-interlacing scanned image (progressive image). Where the digital image signal corresponds to the progressive image, for example, an image of an object of a horizontal stripe pattern corresponds to the image in the original image space 301 in figure 2. On the other hand, where the digital image signal corresponds to the interlaced image, an image which moves greatly corresponds to the image of the original image space 301. In this interlaced image, as shown in figure 2, it sometimes looks like the object has a shape of two outlines.

^{A/50}
~~Besides~~, the original image space 301 may be a region of the object (object region) itself comprising the object, or may be one of plural image spaces (blocks) each comprising a prescribed number of pixels (for example $N \times M$ samples), into which the object region is divided. In this embodiment, for convenience, assume that digital image signals of object regions are sequentially input frame by frame in step S11.

In step S12, the original image space 301 of the digital image signal is resampled to generate plural small image space 401-404. Specifically, every other pixels are extracted in the horizontal direction and pixels on every other pixel row are extracted in the vertical direction in the original image space 301, to generate the four small image

changed into a small image space 406 comprising pixels having sample values in figure 3(b).

Comparing these small image spaces resulting from padding to the odd-numbered field image 381 and the even-numbered field image space 382 (see figure 20) obtained by the prior art method, sample values of pixels in the small image spaces 405 and 406 (see figure 3) are uniform, which shows that high-frequency components ~~is~~ ^{are} not introduced into the image signals of these small images.

In final step S14, it is decided whether or not the resampled original image space corresponds to a final frame of the digital image signal. When decided that the original image space corresponds to the final frame, process in steps S11-S14 are completed (Step S15), whereas when decided that the original image space does not correspond to the final frame, the steps S11-S14 are performed to an original image space corresponding to a subsequent frame.

Thus, in the first embodiment, every other pixels are extracted in the horizontal direction and pixels on every other pixel row are extracted in the vertical direction of the original image space 301 corresponding to the input image signal, and then the extracted plural pixels are rearranged to form 4 small image spaces 401-404, to which padding of pixel values are performed. Therefore, padding is performed to plural small image spaces where there is high

Subsequently, modification^s 1-3 of the first embodiment will be described.

Modification 1 of First Embodiment

Figure 4 is a diagram for explaining a digital image padding method according to a modification 1 of the first embodiment of the present invention and shows flow of image processing in the padding method.

In this digital image padding method of the modification 1 of the first embodiment, ^aprocess for merging pixels in step S16 is added to the steps S11-S15 in the digital padding method of the first embodiment in figure 1.

In step S16, all the pixels in the small image spaces 405 and 406 which have been padded in step S13 are rearranged so that they have the same arrangement as the original image space corresponding to the input digital image signal, to form a merged image space 407 which is as large as the original image space 301 (figure 3(c)).

Specifically, pixels in the small image space 405 obtained by padding the small image space 401 are disposed where odd-numbered pixel columns and odd-numbered pixel rows intersect in the merged image space which is twice as large as the small image space, and pixels in the small image space 406 obtained by padding the small image space 403 are disposed where even-numbered pixel columns and odd-numbered pixel rows intersect in the merged image space. Further, pixels

of the present invention, and shows flow of image processing in the padding method.

The digital image padding method of the modification 2 of the first embodiment, as shown in figure 5, includes step S52 in which the degree of correlation of pixel values between adjacent pixel columns is evaluated for an original image space formed by a resampled input digital image signal, step S53 in which it is decided whether or not the original image space is resampled to form plural small image spaces according to the evaluation result, step S54 in which the original image space is resampled and then the small image space is padded, and step S55 in which the original image space is directly padded.

Subsequently, operation and effect will be described.

In the padding method of the modification 2 of the first embodiment, in step S51, a digital image signal forming a prescribed original image space where pixels are arranged in \sqrt{A} matrix is input. Subsequently in step S52, the degree of correlation of pixel values between adjacent pixel columns is computed for the original image space. More specifically, in this modification, differences of sample values of pixels between each pair of adjacent odd-numbered and even-numbered pixel columns in the original image space are computed, and absolute values of the differences are added for each pair of odd-numbered and even-numbered pixel columns, to

generate first evaluation values.

In addition, differences (first differences) of sample values between each pair of adjacent odd-numbered pixel columns and differences (second differences) of sample values between each pair of adjacent even-numbered pixel columns are computed, and absolute values of these first and second differences are added for each pair of even-numbered pixel columns and for each pair of odd-numbered pixel columns, to generate second evaluation values.

In step S53, comparison is made between the first and second evaluation values. From this comparison result, when the second evaluation values are smaller than the first evaluation values, that is, correlation of pixel values between the odd-numbered and even-numbered pixel columns is lower than correlation of pixel values between odd-numbered pixel columns and between even-numbered pixel columns, in step S54, the original image space is resampled, and then padded. Specifically, pixels on every other pixel column are extracted in the original image space, to generate a first small image space comprising pixels forming odd-numbered pixel columns and a second small image space comprising pixels forming even-numbered pixel columns, and then padding of pixels is performed to each small image space.

On the other hand, when the second evaluation values are not smaller than the first evaluation values from the

evaluation values, and the other functions may be employed. Moreover, the evaluation values may be computed only from significant samples.

Modification 3 of First Embodiment

Figure 6 is a diagram showing a digital image padding method according to a modification 3 of the first embodiment and shows flow of image processing in the padding method.

The digital image padding method of the modification 3 of the first embodiment, as shows in figure 6, includes step S62 in which the degree of correlation of pixel values between adjacent scanning lines (pixel rows) is evaluated for an original image space formed by a sampled input digital image signal, step S63 in which the degree of correlation of pixel values in fields of the original image space is decided, step S64 in which the original image space is resampled to form a small image space corresponding to an odd-numbered field and a small image space corresponding to an even-numbered field, and padding is performed for each small image space, i.e., field by field, and a step S65 in which the original image space is padded frame by frame.

Subsequently, operation and effects will be described.

In the padding method of the modification 3 of the first embodiment, in step S61, a digital image signal forming a prescribed original image space in which pixels are arranged in \sqrt{a} matrix is input. In this modification 3, suppose that

the digital image signal corresponds to the interlaced image, and forms the image space 301 shown in figure 2.

Subsequently in step S62, correlation of pixel values between scanning lines in the original image space is computed. Specifically, by the method described by means of figure 5, first evaluation values indicating correlation of pixel values between odd-numbered and even-numbered lines in the original image space are generated, and second evaluation values indicating correlation of pixel values between odd-numbered lines and between even-numbered lines in the original image space are generated.

Then in step S63, comparison is made between the first and second evaluation values, to decide whether or not correlation of pixel values in fields is higher than correlation of pixel values in a frame.

When decided that the second evaluation values are smaller than the first values, that is, correlation of pixel values in the fields is higher than correlation of pixel values in the frame, in step S64, the original image space formed by the digital image signal is padded field by field. In other words, a small image space composed of odd-numbered lines and a small image space composed of even-numbered lines are generated, and then padding is performed for each small image space (field). On the other hand, when decided that the second evaluation values are not smaller than the first

values, in step S65, the original image space is padded frame by frame, that is, with the odd-numbered lines and the even-numbered lines merged.

Figure 7 is a diagram for explaining field by field padding of the original image space 301 in figure 2. Figure 7(a) shows a small image space 701 corresponding to the odd-numbered field in the original image space 301, and a small ~~image~~ ^{image} space 703 obtained by padding the small image space 701. Figure 7(b) shows a small image space 702 corresponding to an even-numbered field in the original image space 301, and shows a small image space 704 obtained by padding the small image space 702.

As can be seen from figure 7, the small image spaces 701 and 702 can be padded without introducing high-frequency components into them.

In this modification 3 of the first embodiment, it is decided whether the original image space corresponding to the input image digital image signal is padded field by field or frame by frame, and padding of pixel values is performed to the original image space in one of these units. Therefore, it is possible to perform padding to the interlaced image without degrading efficiency in coding of the image signal of to the interlaced image.

Embodiment 2.

Figure 8 is a diagram for explaining a digital image

padding method according to a second embodiment of the present invention, and shows an original image space formed by a digital image signal to be padded, and a padded image space in which the original image space has been padded.

In the digital image padding method of the second embodiment, the step S12 for resampling and step S13 for padding by the digital image padding method of the first embodiment, are replaced by a step in which an original image space 801 corresponding to a digital image signal is directly padded, that is, sample values of insignificant pixels are replaced with padding values obtained from sample values of significant pixels according to a prescribed rule. In this embodiment, used as the significant pixels used in generating the padding values are, pixels which are adjacent to insignificant pixels in the horizontal direction and pixels which are adjacent thereto one pixel spaced apart therefrom in the vertical direction of the original image space.

Specifically, the digital image padding of the second embodiment includes a first replacement step S21 (see figure 8(a)) for sequentially replacing sample values of insignificant pixels in the horizontal direction and a second replacement step S22 (see figure 8(b)) for replacing sample values of insignificant pixels in the vertical direction. In the second replacement step S22, sample values of insignificant pixels in an image space 801a obtained through

*no
this already
was made*

S21

the first replacement step ~~S22~~, are replaced with sample values of pixels on a pixel row adjacent to a pixel row comprising the insignificant pixels, one pixel row spaced apart therefrom.

Subsequently, operation and effects will be described.

Since there is low correlation of pixel values between an odd-numbered line (pixel row) and an even-numbered line (pixel row) in the original image space 801, effectiveness is provided by the method of dividing the original image space 801 into the small image space composed of odd-numbered lines and the small image space composed of even-numbered lines, and padding respective small image spaces, as already described in the first embodiment. On the other hand, for an image signal forming an original image space with high correlation between odd-numbered lines and between even-numbered lines, there is another effective method, in which sample values to be padded, i.e., insignificant pixels in the original image space, are replaced with sample values of significant pixels located one pixel spaced apart therefrom in the vertical direction (one pixel is located adjacently to the other pixel with one pixel interposed between them in the vertical direction).

So, in the digital padding method of the second embodiment, as shown in figure 8(a), sample values of insignificant pixels are replaced with sample values of

embodiment.

Embodiment 3.

Figure 9 is a block diagram showing the image coding apparatus as an image processing apparatus according to the third embodiment of the present invention, wherein figure 9(a) shows an entire construction of the image coding apparatus and figure 9(b) shows a padding section of the image coding apparatus.

An image coding apparatus 100a of the third embodiment includes a blocking unit 101 for dividing an input digital image signal S_g supplied to an input terminal 101a into signals corresponding to blocks each comprising 16×16 pixels as coding units and outputting the resulting image signal (hereinafter referred to as a blocked image signal) B_g , an interlace detecting unit 104 for distinguishing between the interlaced image and the progressive image on the basis of an output B_g of the blocking unit 101, for an image corresponding to the digital image S_g , and outputting a sample identifier D_i according to the result, and a predicting section 120a for producing a prediction image P_{rg} of a target block to-be-coded.

The image coding apparatus 100a further includes a subtracter 102 for outputting difference between the blocked image signal B_g of the target block and the prediction signal P_{rg} as a difference signal (prediction error signal) D_g , data

data
a

compressing ^{device} means 110 for performing information compression to the output Dg of the subtracter 102 according to the sample identifier Di and outputting a compressed difference signal Qg, and a variable length encoder (VLC) 103 for performing variable length coding to the output Qg of the data compressing ^{device} means 110 and outputting a coded image signal Eg.

The data compressing ^{device} means 110 includes a pixel rearrangement unit 113 for rearranging pixels of a difference image signal formed by the difference signal Dg according to the sample identifier Di, a DCT unit 111 for performing discrete cosine transform to an output PDg of the pixel rearrangement unit 113, and a quantizer 112 for quantizing an output Tg of the DCT unit 111 and outputting quantization coefficients as the compressed difference signal Qg. The discrete cosine transform is performed for each of 4 blocks each comprising 8 x 8 pixels into which the block comprising 16 x 16 pixels is divided. Where the rearrangement has been performed, a block 250c is divided into small blocks 251-254 as shown in figure 10(c), whereas where the rearrangement has not been performed, a block 250b is divided into small blocks 255-258 as shown in figure 10(b).

The pixel rearrangement unit 113 is used for rearranging pixels in the image space 250 corresponding to the difference signal Dg to generate a rearranged image space 250a according

to the sample identifier D_i as shown in figure 10(a). In this rearranged image space 250a, an upper region 250a1 comprising 16×8 pixels comprises pixels on odd-numbered pixel rows and a lower region 250a2 comprising 16×8 pixels comprises pixels on even-numbered pixel rows in the image space 250.

The predicting section 120a includes ^{va}data expanding ~~means~~ ^{device} 130 for performing expansion to the output Q_g of the data compressing ~~means~~ ^{device} 110 and outputting an expanded difference signal It_g , and an adder 123 for adding the expanded difference signal It_g to the prediction image signal Prg and outputting a restored image signal Lrg . The data expanding ~~means~~ ^{device} 130 includes an inverse quantizer 121 for inversely quantizing the output Q_g of the data compressing ~~means~~ ^{device} 110, and an IDCT unit 122 for performing inverse DCT to an output IQ_g of the inverse quantizer 121 by transforming data in a frequency domain into data in a spatial domain, and outputting the expanded difference signal It_g .

The predicting section 120a further includes ^{va}padding ~~means~~ ^{device} 150 for performing padding to the restored image signal Lrg from the adder 123 according to the sample identifier D_i , and ^{va}prediction signal producing ~~means~~ ^{device} 140 for producing the prediction image signal Prg from a padded restored image signal Pag .

The prediction signal producing ~~means~~ ^{device} 140 includes a

frame memory 124 for storing the output Pag of the padding ^{device} means 150, a motion detecting unit (ME) 125 for computing a motion vector MV of the target block based on the image data Mg stored in the frame memory 124, the blocked image signal Bg, and the sample identifier Di and outputting the MV, and a motion compensating unit (MC) 126 for generating an address Add1 of the frame memory 124 according to the motion vector MV from the motion detecting unit 125 and outputting an image signal in a memory area of the address Add1 as the prediction signal Prg. The motion detecting unit 125 is used for generating a motion vector of a frame and a motion vector of a field according to the sample identifier Di. The motion vector MV and the sample identifier Di are variable length coded by the variable length encoder 103 together with the compressed difference signal Qg.

As shown in figure 9(b), the padding ^{device} means 150 includes a frame padding unit 128a for padding the output Lrg of the adder 123 frame by frame, a field padding unit 128b for padding the restored image signal Lrg from the adder 123 field by field, a primary switch 127a provided at a primary stage of these padding units, for supplying one of the padding units with the restored image signal Lrg from the adder 123, a secondary switch 127b provided at a next stage of these padding units, for selecting one of outputs Pa1 and Pa2 of respective padding units according to the sample identifier

Di, and a pixel rearrangement unit 129 for receiving a padded restored signal as a selected signal Spa from the secondary switch 127b and rearranging pixels in an image space formed by the padded restored image signal.

As shown in figure 10(b), the frame padding unit 128a is used for performing padding the restored image signal Lrg of 4 small blocks (8 x 8 pixels) 255-258 in an image space 250b (16 x 16 pixels) corresponding to the restored image signal at a time. As shown in figure 10(c), the field padding unit 128b is used for performing padding to the restored image signal Lrg of small blocks 251 and 252 composed of first field lines in an upper region 250c1 of an image space 250c of the restored image signal at a time, and padding the signal Lrg of small blocks 253 and 254 composed of second field lines in a lower region 250c2 of the image space 250c at a time. The pixel rearrangement unit 129 is used for rearranging pixels in an image space 250d corresponding to a padded restored image signal from the field padding unit 128b and outputting the image signal Pag corresponding to a merged restored image space 250e where 8 pixel rows in the upper region 250d1 and 8 pixel rows in the lower region 250d2 of the image space 250d are alternately arranged.

Next,^{va} data structure of a coded image signal output from the image coding apparatus 100a will now be described. Figure 11 schematically shows a data structure of the coded

image signal (bit stream).

In this bit stream 200, a bit string F corresponding to a frame image comprises a synchronous image signal 203 indicative of a starting point of a code string, a quantization step value 204 indicative of a quantization scale (quantization step) for use by quantization in coding process, and data D(1), D(2), (D3), ..., D(i), corresponding to blocks (macroblocks) MB(1), MB(2), MB(3), ..., MB(i) each comprising 16 x 16 pixels. Reference numerals 205, 208, and 211 designate sample identifiers each indicates ^{ing} whether or not correlation between pixels in fields is higher than correlation between pixel values in a frame. Reference numerals 206, 209, and 212 designate variable length coded motion vectors. Reference numerals 207, 210, and 213 designate DCT coefficients of subblocks each comprising 8 x 8 pixels of each block. The data D(1), data D(2), and D(3) corresponding to respective macro blocks comprises, the sample identifier 205, the motion vector 206, and the DCT coefficient 207, the sample identifier 208, the motion vector 209, and the DCT coefficient 210, and the sample identifier 211, the motion vector 212, and the DCT coefficient 213, respectively. In figure 11, reference numeral 214 designates a synchronous image signal of a frame subsequent to the frame F.

In this embodiment, the synchronous image signals 203

When the difference signal D_g is supplied to the data compressing ^{device} means 110, the pixel rearrangement unit 113 subjects the difference signal D_g to rearrangement according to the sample identifier D_i . Specifically, where the digital image signal corresponds to the interlaced image, the difference signal D_g is subjected to rearrangement and input to the DCT unit 111, whereas where the digital image signal corresponds to the progressive image, the difference signal D_g is directly input to the DCT unit 111 without rearrangement. The DCT unit 111 performs DCT to the output PD_g of the pixel rearrangement unit 113. More specifically, for the block corresponding to the interlaced image, the block is divided into subblock as shown in figure 10(c), and for the block corresponding to the progressive image, the block is divided into subblocks as shown in figure 10(b), and then the output PD_g is subjected to DCT for each subblock. The quantizer 112 quantizes an output T_g of the DCT unit 111 by a quantization step and outputs quantization coefficients Q_g of the difference signal to the variable length encoder 103 and the information expanding section 130.

The information expanding section 130 expands and converts the compressed difference signal Q_g of the target block into the expanded difference signal IT_g . More specifically, in this embodiment, the inverse quantizer 121 inversely quantizes the compressed difference signal Q_g , and

further, the inverse discrete cosine transform (IDCT) unit 122 subjects the output IQg of the quantizer 121 to IDCT by transforming a signal in a frequency domain into a signal into a signal in a spatial domain.

The adder 123 adds the expanded difference signal ITg to the prediction image signal Prg and outputs the restored image signal Lrg to the padding means 150.

In the padding ^{device} means 150, the restored image signal Lrg is supplied to one of the frame padding unit 128a and the field padding unit 128b through the switch 127a. At this time, switching of the switch 127a is controlled according to the sample identifier Di. Where a value of the sample identifier Di is 1, that is, there is high correlation between pixels in the fields, the restored image signal Lrg is supplied to the field padding unit 128b through the switch 127a and is subjected to intra-field padding therein. Specifically, as shown in figure 10(c), padding is performed to the restored image signals of small blocks 251 and 252 composed of lines of the first field of the restored image space 250c at a time, and the restored image signals of small blocks 253 and 254 composed of lines of the second field of the restored image space 250c at a time.

On the other hand, where the value of the sample identifier Di is 0, that is, where there is high correlation between pixel values in the frame, the restored image signal

progressive image. Therefore, it is possible to perform differential coding to the interlaced image with high efficiency.

Subsequently, modifications of the third embodiment will be described.

Modification 1 of Third Embodiment

Figure 12 is a diagram showing an image coding apparatus according to a modification 1 of the third embodiment.

In an image coding apparatus 100b of the modification 1 of the third embodiment, only a predicting section 120b differs from that of the image coding apparatus 100a of the third embodiment, and in the predicting section 120b of the image coding apparatus 100b, the padding ^{device} means 150 of the predicting section 120a of the first embodiment is replaced with a merging unit 151 which performs merging wherein pixels in an image space formed by the restored image signal Lrg from the adder 123 are rearranged, and ^{device} padding means 150b which performs padding to an output of the merging unit 151.

The merging unit 151 is, as shown in figure 10(d), used for rearranging pixels by alternately arranging pixels rows in the upper region 250d1 and pixel rows in the lower region 250d2 of the image space 250d. The padding ^{device} means 150b includes the primary and secondary switches 127a and 127b, the frame padding unit 128a, and the field padding unit 128b of the padding ^{device} means 150 of the third embodiment, the field

padding unit 128b performing padding by the digital image padding method of the second embodiment. The other components are identical to those of the third embodiment.

In the modification 1 of the third embodiment thus constructed, the same effects as provided by the third embodiment are obtained.

Modification 2 of Third Embodiment

8 Figure 13 is a diagram showing an image coding apparatus according to a modification of the third embodiment of the present invention, wherein figure 13(a) shows an entire construction of the image coding apparatus and figure 13(b) shows ^{va}padding ^{device} means 150c of the data compressing ^{device} means 110c of the image coding apparatus.

14 In an image coding apparatus 100c of the modification 2 of the third embodiment, only ^{va}data compressing ^{device} means 100c differs from that of the image coding apparatus 100a of the third embodiment, and the data compressing ^{device} means 110c of the image coding apparatus 100c is provided with ^{va}padding ^{device} means 150c which performs padding to an output PDg of the pixel rearrangement unit 113 between the pixel rearrangement unit 113 and the DCT unit 111 at the next stage of the data compressing ^{device} means 110 of the third embodiment.

25 The padding ^{device} means 150c includes a frame padding unit 158a for performing padding to the output PDg of the rearrangement unit 113 frame by frame, a field padding unit

158b for performing padding to the output PDg of the rearrangement unit 113 field by field, a primary switch 157a provided at a previous stage of these padding units, for supplying one of these padding units with the output PDg according to the sample identifier Di, and a secondary switch 157b provided at a next stage of these padding units, for selecting one of outputs PDg1 and PDg2 of the padding units according to the sample identifier Di. Constructions of the frame padding unit 158a and the field padding unit 158b are identical to those of the frame padding unit 128a and the field padding unit 128b of the third embodiment.

In this modification 2 of the third embodiment, since padded difference signal is supplied to the DCT unit 111, efficiency in DCD process is increased, in addition to the effects provided by the third embodiment.

Embodiment 4.

Figure 14 is a block diagram showing an image decoding apparatus according to a fourth embodiment of the present invention.

An image decoding apparatus 900a of the fourth embodiment is used to receive a bit stream 200 of the data structure in figure 11 as a coded image signal Eg in which an image signal has been compressively coded and perform decoding to the coded image signal Eg.

Specifically, the image decoding apparatus 900a

includes a data analyzing unit 902 for receiving a coded difference signal Eg of a target block to be decoded (target block), and performing analysis and variable length decoding to the coded difference signal Eg, ^{via} data expanding ^{device} means 903 for expanding an output AEg of the data analyzing unit 902 and outputting an expanded image signal DEg, an adder 906 for adding the output DEg to a prediction image signal Pg2 of the target block, an inverse blocking unit 907 for integrating reproduced image signals of respective blocks as an output PEg of the adder 906 and outputting an image output signal REg of a scanning line structure, and a predicting section 910a for producing the prediction image signal Pg2.

14 The data expanding ^{device} means 903 comprises an inverse quantizer 904 for inversely quantizing the output AEg of the data analyzing unit 902, and an IDCT unit 905 for performing IDCT (inverse discrete cosine transform) as one type of inverse frequency transform, to the output DEg1 of the inverse quantizer 904, and outputting the expanded difference image signal DEg.

21 The predicting section 910a includes padding ^{via} ^{device} means 920a for performing padding to the output PEg of the adder 906, a frame memory 909 which contains an output Pa of the padding ^{device} means 920a as a reproduced image signal, and a motion compensating unit 911 for generating an address Add2 of the

frame memory 909 according to an output Rg2 of the frame memory 909 and a motion vector MV of the block which has been decoded by the data analyzing unit 902, and reading a prediction image signal Pg2 of the target block from the frame memory 909 which contains recorded data Rg2 using the address Add2.

The padding ^{device} means 920a includes a frame padding unit 921a for performing padding to the output PEg of the adder 906 frame by frame, a field padding unit 921b for performing padding to the output PEg field by field, a primary switch 922 provided at a previous stage of these padding units, for supplying one of them with the output PEg according to the sample identifier Di from the data analyzing unit 902, a secondary switch 923 provided at a next stage thereof, for selecting one of outputs Pa1 and Pa2 of respective padding units according to the sample identifier, and a pixel rearrangement unit 924 for rearranging pixels of the padded image signal as a selected signal Pas from the secondary switch 923.

Besides, reference numerals 901a and 901b designate input and output terminals of the image decoding apparatus 900a, respectively.

Subsequently, operation will be described.

When the compressively coded image signal Eg, for example, the bit stream 200 in figure 11 is input to the input terminal 901a, the data analyzing unit 902 performs variable

length decoding to the coded image signal by analysis. The resulting decoded data is output to the data expanding ^{device} means 903 as a compressed difference signal AEg in which a quantization step or a DCT coefficient has been compressed. The data analyzing unit 902 also outputs the motion vector MV and the sample identifier Di to the predicting section 910a.

The data expanding ^{device} means 903 expands the compressed difference signal to be restored to an expanded difference signal of the target block. Specifically, the inverse quantizer 904 inversely quantizes the compressed difference signal, and then the IDCT unit 905 performs inverse frequency transform to the output DEg1 of the quantizer 904, by transforming a signal in a frequency domain into a signal in a spatial domain.

The motion compensating unit 911 generates the address Add2 for accessing the frame memory 909 according to motion vector MV from the data analyzing unit 902 and extracts the prediction image signal Pg2 of the target block from the reproduced image signal stored in the frame memory 909. The adder 906 adds the output DEg of the data expanding ^{device} means to the prediction image signal Pg2 and outputs the reproduced image signal PEg of the target block.

The reproduced image signal is supplied to the inverse blocking unit 907 and the predicting section 910a.

those of the image decoding apparatus 900a of the fourth embodiment in figure 14.

In the image decoding apparatus 900b, the predicting section 910a of the image decoding apparatus 900a of the fourth embodiment is replaced by a predicting section 910b which differs in construction from the same.

In the predicting section 910b, there is provided ^{va} padding ^{device} means 920b between a motion compensating unit 911 and an adder 906, for performing padding to a motion compensated prediction image signal Pg2 and supplying the resulting signal to the adder 906. The padding ^{device} means 920b includes a frame padding unit 921a, a field padding unit 921b, a primary switch 922 for supplying one of these padding units with the prediction image signal Pg2 from the motion compensating unit 911 according to the sample identifier Di, and a secondary switch 923 for selecting one of outputs of the padding units according to the sample identifier Di and outputting a selected signal to the adder 906.

Subsequently, operation and effects will be described.

Motion compensation is performed to the interlaced image frame by frame or field by field. The frame by frame motion compensation is performed by obtaining a prediction image signal from a frame, while the field by field motion compensation is performed by obtaining prediction image signals from the corresponding first and second fields

separately.

The image decoding apparatus 900b according to the modification 1 of the fourth embodiment provides effectiveness in the field by field motion compensation. In the image decoding apparatus 900b, switching of the primary switch 922 is controlled according to the sample identifier Di from the data analyzing unit 902, and the output of the motion compensating unit 911 is input to one of the frame padding unit 921a and the field padding unit 921b. The prediction image signal is padded by one of these padding units and supplied to the adder 906.

In this modification 1 of the fourth embodiment, since padding is performed to the prediction image signal fetched from the frame memory 909, amount of signals to-be-padded in the predicting section can be reduced, as compared to a case where padding is performed to all the reproduced image signals stored in the frame memory 909.

Modification 2 of Fourth Embodiment

Figure 16 is a block diagram showing an image decoding apparatus according to modification 2 of the fourth embodiment. An image decoding apparatus 900c according to the modification 2 of the fourth embodiment has constructions of the image decoding apparatus 900a of the fourth embodiment and the image decoding apparatus 900b of its modification 1 in combination. In other words, in addition to the

predicting section 910a comprising the padding ^{device} means 920a of the image decoding apparatus 900a of the fourth embodiment, the image decoding apparatus 900c includes ^{van} auxiliary padding ^{device} means (second padding ^{device} means) 920c2 provided at a next stage of the motion compensating unit 911, the output of which is output to the adder 906. Here it is assumed that constructions of the first and second padding ^{devices} means 920c1 and 920c2 are identical to those of the padding ^{device} means 920a of the fourth embodiment and the padding ^{device} means 920b of the modification 1 of the fourth embodiment, respectively.

In the modification 2 of the fourth embodiment thus constructed, the first and second padding ^{devices} means 920c1 and 920c can share padding, whereby padding can be performed in the predicting section with higher efficiency.

Furthermore, a program for implementing the digital image padding method or the image processing apparatus shown in each of the embodiments is recorded in a data recording medium such as a floppy disc, whereby processing is performed with ease in an independent computer system.

Figure 17 is a diagram showing a case where image processing of the digital padding method, or image coding or image decoding of the image processing apparatus in the above embodiments is performed in a computer system by the use of a floppy disc which contains a program of these image processing.

Figure 17(b) shows a front appearance and a cross-section of a floppy disc FD, and a floppy disc body as a recording medium. Figure 17(a) shows a physical format of the floppy disc body D. The floppy disc body D is stored in a case F, and in a surface of the disc body D, plural tracks Trs are formed from outer to inner radius thereof, each track being divided into 16 sectors Se in angle direction. Therefore, in the floppy disc body D which contains the program, data of the program is recorded in an allocated region of the floppy disc FD.

Figure 17(c) shows a construction of recording and reproducing the program in/from the floppy disc FD. In case of recording the program in the floppy disc FD, the data of the program is written thereto through the floppy disc drive FDD from the computer system Cs. In another case of constructing the image decoding method in the computer system Cs by the program in the floppy disc FD, the program is read from the floppy disc FD by the use of the floppy disc drive FDD and transferred to the computer system Cs.

While description has been given of image processing in a computer system by the use of the floppy disc as the data recording medium, this image processing can be also performed by the use of an optical disc. Besides, the recording medium is not limited to this, and an IC card, a ROM cassette, and so forth, may be used so long as they can

record a program therein.

Industrial ^{Applicability} ~~Availability~~

As described above, the digital image padding method, the image processing apparatus, and the data recording medium of the present invention, can increase coding efficiency in compression of an image signal, they are very useful in implementing coding or image decoding in a system which transmits/stores the image signal, and simultaneously they are suitable for compression and expansion of a moving picture according to a standard such as MPEG4.

ABSTRACT

In a digital image padding method according to the present invention, as shown in figure 2, every other pixels in an original image space ~~301~~ corresponding to an input digital image signal are extracted in the horizontal direction, and every other pixels are extracted in the vertical direction, the extracted plural pixels are rearranged to form four small image spaces ~~401-404~~, and pixels values in these small image spaces are padded.

In the digital image padding method thus constructed, padding of pixel values is performed to plural small image spaces where there is high correlation of pixel values between adjacent scanning lines rather than to an original image space where there is low correlation of pixel values between adjacent scanning lines. That is, in the padded small image spaces, there is high correlation of the pixel values. As a result, it is possible to avoid introduction of high-frequency components into the digital image signal of the interlaced image, and hence, differential coding or differential decoding can be performed to the interlaced image or the like with high coding efficiency while suppressing degradation of coding efficiency resulting from padding.

Version with Markings to Show Changes Made

1. (Amended) A digital image padding method in which padding of pixel values is performed to a digital image signal forming an original image space including [comprising] an image having an arbitrary shape and containing [comprising] significant pixels and insignificant pixels, said method comprising:

a pixel rearrangement [step] in which plural pixels in the original image space are grouped [according to a prescribed rule] to form plural small image spaces each comprising pixels of the same group so that a pixel value correlation within the small image spaces becomes higher than a pixel value correlation within the original image space; and

a pixel padding [step] in which values of insignificant pixels in each of the small image [space] spaces obtained by said pixel rearrangement are replaced with padding pixel values generated on the basis of the significant pixel values in each of the small image spaces [by a prescribed method].

2. (Amended) The digital image padding method of claim 1, wherein in said pixel rearrangement [step], sampling is performed by extracting pixels every (N+1)-th (N is a [:] positive integer) pixel in a prescribed direction of the original image space (N+1) times by using [the] first to [the] (N+1)-th pixels as starting sample pixels[,] to form (N+1) pieces of small image spaces each comprising a prescribed number of pixels obtained by one padding.

3. (Amended) The digital image padding method of claim 2, wherein operation values obtained by performing operation on values of significant pixels in an n-th (n=1, 2, . . . , N+1) small image space are used as the padding pixel values for replacing the values of insignificant pixels in the n-th small image space.

6. (Amended) The digital image padding method of claim 1, wherein in said pixel rearrangement [step], sampling is continuously performed twice using [the] first and second pixel rows as starting sample pixel rows [,] by extracting pixels on every other pixel row in a [the] vertical direction of the original image space [,] to form first and second small image spaces each comprising a prescribed number of pixels obtained by first and second samplings, respectively.

7. (Amended) A digital image padding method in which padding of pixel values is performed to an interlaced [a] digital image signal forming an original image space including [comprising] an image having an arbitrary shape and containing [comprising] significant pixels and insignificant pixels, said method comprising [the steps of]:

dividing the original image space into a first small image space comprising pixels on odd-numbered pixel rows in the original image space and a second small image space comprising pixels on even-numbered pixel rows in the original image space; and

generating first padding pixel values from values of significant pixels in the first small image space and replacing values of insignificant pixels in the first small image space with the first padding pixel values, and generating second padding pixel values from values of significant pixels in the second small image space and replacing values of insignificant pixels in the second small image space with the second padding pixel values.